


JUPITER

ITEM: MB14021212004

CCT: 3500 4000 5000 5700 6500K
(SELECTABLE)



Unit: mm



High on Efficacy

Over %50 energy savings than traditionally fluorescent fixtures, low heat productions requires less maintenance and operation cost



WIDE APPLICATION

Suitable for private offices, open office areas, upscale retail applications, public circulation areas, and school.



NON INTEGRATED ISOLATED DRIVER

Driver is fixed on the back of the panel or side to prevent mis-handling during shipment.



HIGHER LIFE

5 Years Limited Warranty, Rated for 50,000 hours



WIDE OPERATING VOLTAGE / RATED VOLTAGE

120...347V
50/60HZ



CERTIFICATE

ETL, DLC, FCC, RoHS, CEL

APPLICATIONS

Offices

Schools

Hospitals

Software Centres

Commercial space

SPECIFICATIONS:

THD: ≤%20	IP: 40
CUTOUT(MM): 1163x253	RA: 80
CATEGORY: PANEL Lamp	BEAM ANGLE: 120°
HIGHER ENERGY SAVING: 125 IM/W	TEMPERA : -4°F to 113°F (-20°C to 45°C)
DIMENSION: L: 1213 "H: 35 "W: 303	WATT: 15 20 25 30 40W (SELECTABLE)