



JUPITER

ITEM: MB14021201002

CCT: 3500 4000 5000 5700 6500K
(SELECTABLE)



High on Efficacy

Over %50 energy savings than traditionally fluorescent fixtures, low heat productions requires less maintenance and operation cost



WIDE APPLICATION

Suitable for private offices, open office areas, upscale retail applications, public circulation areas, and school.



NON INTEGRATED ISOLATED DRIVER

Driver is fixed on the back of the panel or side to prevent mis-handling during shipment.



HIGHER LIFE

5 Years Limited Warranty, Rated for 50,000 hours



WIDE OPERATING VOLTAGE / RATED VOLTAGE

120 - 347V
50/60 HZ



CERTIFICATE

ETL, DLC, FCC, RoHS, CEL

APPLICATIONS

Offices

Schools

Hospitals

Software Centres

Commercial space

SPECIFICATIONS:

THD: ≤%20

IP: 40

CUTOUT(MM): 1163x553

RA: 80

CATEGORY: PANEL Lamp

BEAM ANGLE: 120°

HIGHER ENERGY SAVING: 125 IM/W

TEMPERA : -4°F to 113°F (-20°C to 45°C)

DIMENSION: L: 1213 "H: 35 "W: 603

WATT: 30 40 50 60 72W (SELECTABLE)